



**IEC-61243-1**  
Edition 2  
October 2003



## DESCRIPTION

IEC electronic voltage detector "Ultra compact series" for indoor and outdoor use.  
Ultimate "head capacitive technology" of voltage detector.  
Universal application 50 / 60 Hz and wide band of voltage.  
Maximum voltage range :  $Un_{max} / Un_{min} = 3.6$

## OPERATING CONDITIONS

### Voltage presence is indicated by :

- Red flashing LED (very bright, visible at more than 20 m in direct lighting).
- Powerful rated audible signal > 67 dB (A) / 1.5 m.

### Operating check :

- By pressing the Test button, correct operation is indicated by red LED flashing on and a sound signal.
- After releasing the Test button, a timed green LED lights on.  
It indicates the good working order of the detector.

## CHARACTERISTICS

- |  |  |
|--|--|
| <ul style="list-style-type: none"><li>• Nominal range: see below .</li><li>• Dielectrically tested on substation bars.</li><li>• Precise and stable operating threshold.</li><li>• Reduced sensitivity to induced voltages and to interference field.</li><li>• High environmental resistance (impacts, vibrations, moisture).</li><li>• Robust thermoplastic housing.</li></ul> | <ul style="list-style-type: none"><li>• Temperature conditions: class N (-25 to 55°C)</li><li>• Power supply: 1 standard 9 V battery 6LR61</li><li>• Network frequencies : 50 and 60 Hz</li><li>• Dimensions of the detector: Ø 59 x 270 mm.</li><li>• Weight of the detector: 0,35 kg.</li><li>• Contact electrodes fitted to the body by screwing and easily interchangeable.</li><li>• Packaging: supplied in a caring bag</li><li>• In compliance with the standard CEI 61243-1 Ed 2 (2003).</li></ul> |
|--|--|

**End fitting :**

End fitting "C": hexagonal male 12 mm on flats, for hexagonal end fitting sticks.  
(CC-765-xx/yy-C)



End fitting "K": for Universal end fitting sticks  
(CC-765-xx/yy-K)

**Technical details :**

**Main references**

References	Un <sub>min</sub> (xx)	Un <sub>Max</sub> (yy)
CC-765-10/30-(* )	10 kV	30 kV
CC-765-10/36-(* )	10 kV	36 kV
CC-765-3/10-(* )	3 kV	10 kV
CC-765- 5,5/20-(* )	5,5 kV	20 kV
CC-765-15/45-(* )	15 kV	45 kV
CC-765-5/18-(* )	5 kV	18 kV

(\* ) End fitting : C or K

**Other voltage range are available : contact us for more information**