



Safety Data Sheet

PERMABOND ET540 B

Revision Number: 1

Issue date: 05/05/15

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:PERMABOND ET540 BProduct Type:Epoxy Hardener

Company: PERMABOND LLC 14 Robinson Street Pottstown, PA 19464 USA Telephone: 732-868-1372 or 800-640-7599 Website: www.permabond.com

Emergency Telephone:

Medical: Poison Control Center 866-827-6282 (toll free) or 303-389-1109 Transport: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

WARNING:

CAUSES SKIN IRRITATION CAUSES SERIOUS EYE IRRITATION MAY CAUSE AN ALLERGIC SKIN REACTION

	HAZARD CLASS	HAZARD CATEGORY
SERIOUS EYE IRRITATION		2
SKIN IRRITATION		2
SKIN SENSITIZATION		1
	PICTOGRAM(S)	
Precautionary Statements		
Prevention:		spray. Wash thoroughly after handling. Wear protective aminated clothing should laundered separately.
Response:	to fresh air and keep comfortable with plenty of water for several r do. Continue rinsing. Immediatel IF ON SKIN: Immediately remov	DO NOT induce vomiting. IF INHALED: Remove person e for breathing. IF IN EYES: Immediately rinse cautiously minutes. Remove contact lenses, if present and easy to y call a poison control center or a physician. ve contaminated clothing. Rinse with plenty of soap and et medical attention. Wash contaminated clothing before
Storage:	Store locked up.	

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).



Disposal:	Dispose of according to Federal, State/Provincial and local governmental regulations.
Existing conditions aggravated by exposure:	Skin, eye and respiratory disorders.

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	CONCENTRATION (%)*	
Polyamide resin	68410-23-1	60 – 100	
Triethylenetetramine	112-24-3	1 – 5	

*Exact concentration is a trade secret. Concentration ranges are provided to assist user in determining appropriate protection.

4. FIRST	AID	MEASURES	

Inhalation:	Move to fresh air. If breathing is difficult give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	Immediately wash with soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms develop and persist. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush with large amounts of water for at least 15 minutes. Get immediate medical attention.
Ingestion:	Do not induce vomiting. Keep individual calm and get medical attention. Never give anything by mouth to an unconscious person.
Symptoms:	See section 11

5. FIRE-FIGHTING MEASURES

Extinguishing media:	Water spray or fog, dry chemical or carbon dioxide.
Special fire fighting procedures:	Wear self-contained breathing apparatus and protective clothing. In case of fire keep container cool with water spray.
Unusual fire or explosion hazards:	Keep container cool with water spray. Uncontrolled polymerization may occur at high temperature resulting in explosions or rupturing containers.
Hazardous combustion products:	Toxic and/or irritating organic vapors may be generated. Oxides of carbon. Oxides of nitrogen. Amines.



6. ACCIDENTAL RELEASE MEASURES

Use personal protection equipment recommended in section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Remove sources of ignition. Prevent product from entering drains or waterways.
Clean-up methods:	Dyke spill to prevent from entering water ways. Ventilate area. Wear protective equipment to clean up. Soak up spill using absorbent material such as sand, silica gel, acid binder, universal binder, or saw dust. Scrape as much material as possible and store in partially filled container until disposal. Refer to section 8 (Exposure Controls/ Personal Protection) before clean up

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container tightly closed. Keep away from heat, sparks and flames.
Storage:	Store in original container in a cool well ventilated area away from heat, sparks, and flames. For safe storage, store below 37.8(100°F). For shelf life information contact Permabond customer service at (800)714-0170

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employees should complete an assessment of all workplaces to determine the need for and selection of proper exposure controls and protective equipment before each task is started.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyamide resin	None	None	None	None
Triethylenetetramine	None	None	1 ppm (6 gm/m3) TWA (skin)	None
Engineering controls:	Use local exhaust ventilation to m	aintain worker expos	sure below established exposu	re limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).			
Skin protection:	Use chemical resistant/ impermeable gloves and protective clothing to prevent skin contact.			
Eye/face protection:	Safety goggles or safety glasses with side shields.			

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous liquid
Color:	Amber
Odor: Odor threshold: pH: Vapor pressure:	Ammoniacal Not Available Not applicable Not available



Boiling point/range:	Not available
Melting point/range:	Not available
Specific gravity:	1.1
Vapor density: Flash point: Flammable/Explosive limits – Lower: Flammable/Explosive limits – upper: Autoignition Temperature: Evaporation rate:	Not available >100°C (>212°F) Not available Not available Not available Not available
Solubility in water:	Slight
Partition coefficient (n-octanol/water): Decomposition temperature: VOC content:	Not available Not available <2 %, 20 grams/liter (Estimated) (for resin and hardener mixed together)

10. STABILITY AND REACTIVITY

Stability:	Stable when stored under the recommended storage conditions
Hazardous reactions:	None under normal processing conditions. In the presence incompatible materials or high temperature polymerization may occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Amines Irritating organic vapors.
Incompatible materials:	Strong oxidizing agents. Strong bases. Strong acids.
Conditions to avoid:	Contact with incompatible materials which may cause polymerization. Excessive heat.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors may cause allergic respiratory reaction. Inhalation of vapor or mist may cause mild respiratory track irritation.
Skin contact:	May cause skin burns. Allergic skin reaction.
Eye contact:	Causes serious eye damage.
Ingestion:	Causes burns. May cause burns of the mouth and throat.

Hazardous components	LD50	LC50	Immediate and delayed Health Effects
Polyamide resin	None available	None available	No records available
Triethylenetetramine	LD50 – ORAL (RAT) 2,500 mg/Kg LD50 – DERMAL (RABBIT) 550 mg/Kg	None	Allergen, Corrosive, Irritant

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyamide resin	No	No	No
Triethylenetetramine	No	No	No



12. ECOLOGICAL INFORMATION

Ecological information:

Not Available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State/Provincial and local governmental regulations. Refer to section 8 (Exposure Controls/Personal Protection) before handling.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions: Amines, liquids corrosive, n.o.s. (contains tetraethylenetetramine)

International Air Transportation (ICAO/IATA):

Proper shipping name: Hazard class or division: Identification number: Packing group: Amines, liquids corrosive, n.o.s. (contains tetraethylenetetramine)

Water Transportation (IMO/IMDG):

Proper shipping name: Hazard class or division: Identification number: Packing group: Marine pollutant: Amines, liquids corrosive, n.o.s. (contains tetraethylenetetramine)

No

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

TSCA 12 (b) Export Notification: CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:

CERCLA Reportable quantity:

California Proposition 65:

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above the reporting limits. None above the reporting limits. Immediate Health, Delayed Health, Fire, Reactive This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

No chemical listed on the California Proposition 65 are known to be present.



Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous one: New format

Issue date: 05/05/15

ADDITIONAL INFORMATION: The information given and the recommendations made herein apply to our product(s) alone and are not combined with other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guaranty of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.