

905 DIGITAL TERRESTRIAL EQUIPMENT 905-TO



Power supply units



FA-310



FA-312

Description

Switching power supply, which permits the installation of an amplifier and different modules on the support frame. Power supply with a flat cable of 20 lines for different feed voltages.

Applications

Required for feeding the modules of the equipment.

Characteristics

Protected against power surges, overloads and short-circuits. Zamak chassis with side gills to facilitate proper ventilation. Supplied with power cable.

CODE		9120046				9120168			
MODEL		FA-310				FA-312			
Output voltage	V \cdots	+3.3	+5.2	+12.0	+24	+3.3	+5.2	+12.0	+24
	mA	5500	2500	1500	500	10000	5000	1500	500
Peak to peak ripple voltage	mV	>50				100			
Mains voltage	V \sim	230 \pm 20% 50/60 Hz		240 +15% 50/60 Hz -20% 50/60 Hz		90..264 50/60 Hz			
	W	72				85			
Operating temp. close to equipment	$^{\circ}$ C	-10..+65							
Room temperature with/without fan	$^{\circ}$ C	-10..+55/+45							
Protection index		IP 20C							
Units per packaging		1							
Packing weight	Kg	1.43				1.65			
Packing dimensions	mm	270 x 165 x 60							

See table on page 454 for more information